

34R TYYPPIKÄYRÄT



Läpäisyarvot (%)

Lajite:	0 / 2	0 / 4	2 / 5	4 / 8	4 / 12	8 / 16
Seula (mm#):	G _{f85}	G _{f85}	G _{C 85/20}	G _{C 85/20}	G _{C 90/15}	G _{C 85/20}
0.063	7	4	1	1	1	1
0.125	14	8	2	2	2	2
0.25	26	14	2	2	2	2
0.5	42	22	2	2	2	2
1	68	34	2	2	2	2
2	95	52	13	2	2	2
4	100	85	70	5	5	2
5.6	100	98	98	27	10	
8	100	100	100	95	40	10
12.5	100	100	100	100	95	
16	100	100	100	100	100	95
32	100	100	100	100	100	100
64	100	100	100	100	100	100
H	745	615	491	410	355	317

Päiväys: 21.1.2015

Tuotannon sallitut poikkeamat täyttävät sekä by 43:n että standardin SFS-EN 12620 vaatimukset.

Lajite:	0 / 2	0 / 4	2 / 5	4 / 8	4 / 12	8 / 16
Seula (mm#):	G _{f85}	G _{f85}	G _{C 85/20}	G _{C 85/20}	G _{C 90/15}	G _{C 85/20}
0.063	± 3	± 3	± 1	± 1	± 1	± 1
0.125	± 3	± 3	± 2	± 2	± 2	± 2
0.25	± 4	± 4	± 2	± 2	± 2	± 3
0.5	± 5	± 5	± 2	± 2	± 2	± 5
1	± 8	± 6	± 2	± 2	± 2	± 5
2	± 5	± 8	± 5	± 2	± 2	± 5
4		± 5	± 7	± 5	± 5	± 5
5.6		± 5	± 5	± 6		
8				± 5	± 10	± 10
12.5					± 5	
16						± 5
32						
64						

