

**DECLARATION OF PERFORMANCE**

**No.: 0840-CPR-7647-090080-08**

1. Unique identification code of the product-type:  
**Phthalocyanine Blue, Ferroxon  
EN 12878 - Blue Pigment**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
**See packaging of the construction product**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Colouring of building materials based on cement and/or lime**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
**Registered trade mark: Ferroxon  
Contact address: Schlieper & Heyng GmbH & Co. KG  
Gewerbegebiet Talstraße  
D 57647 Nistertal**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
**Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 2+**
7. I In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**The notified body „Forschungsinstitut der Zementindustrie GmbH“ (NB 0840) conducted the initial inspection of the manufacturing and of factory production control as well as the continuous surveillances, assessment and evaluation of factory production control in accordance to sytem 2+ and certified the factory production control.**
8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**Not applicable**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Setting time	passed	EN 12878:2013
Compressive strength	Category A, max. -50 %	
Composition	passed	
water soluble substances	Category A, max. 5,6 %	
Soluble chloride	Category A, max. 0,1 %	
Total chloride	Category A, max. 0,1 %	
Loss on ignition	see technical data sheet	
pH value	see technical data sheet	
Resistance to weathering	passed	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Ralf Hög, Managing Director


---

(name und function)

Nistertal, 12.09.2013

---

(place and date of issue)



---

(signature)